

ALLINWOOD ENGINEERED WOOD FLOORING

DESCRIPTION

This product is manufactured in compliance with EN 13489:2002, European Norm for multi-layer parquet elements.

Product: 3-layer European Oak Engineered Flooring.

COMPOSITION

Structure consists of:

Top Layer: European White Oak lamella 3.2 mm

Core Layer: Finger-jointed pine or oak blocks

Backing Layer: Pine veneer

Surface finished with eco-friendly oxidative hardwax oil, ensuring the highest environmental standards. Made in Europe with certified materials.

GRADE CLASSIFICATION

A (Prime): Clear, minimal knots (max. Ø 5mm), no sapwood, no end cracks

AB (Select): Healthy knots (max. Ø 15mm), slight variation, no sapwood

ABC (Natural): Filled knots (max. Ø 30mm), light variation, occasional sapwood

ABCD (Rustic): Filled knots (max. Ø 50mm), full variation, occasional sapwood

CD (Wild Rustic): Unlimited filled knots, color/sapwood allowed, no end cracks

TECHNICAL FEATURES

Surface: Brushed & Oiled Rubio Monocoat®

Profiling System: Tongue & Groove, 4-sided micro bevel

Formaldehyde Emission: E1 compliant & M1 VOC Free

Indoor Air Quality: A+ , EMICODE EC1 Plus, Greenguard Gold (California01350), Ü Label - DIBT

Living Building Challenge (LBC): Red List Free: products are safe for the human health and the greater environment

Noise & Impact Isolation(UNE-EN-ISO 140-8) Lw:17 db

Thermal Conductivity (EN 12664): ~0.14 W/m·K

Suitable for: Residential & light commercial use

Underfloor Heating: Compatible, max surface temp 75F , RH 40-60%. Install per guidelines to maintain warranty.

MAINTENANCE

Use wood floor soap and maintenance oil recommended for oiled surfaces. Avoid excessive moisture. Periodic oil refresh recommended for long-term beauty.

WARRANTY

25-year residential warranty.

5-year light commercial warranty.

See full warranty terms at: www.allinwoodusa.com



DIMENSIONS

Thickness	Width	Length Range
9/16" (14mm)	6 5/16" (160mm)	84 5/8"-94 1/16" (2150-2390mm)
	7 1/4"-7 1/2" (185/190mm)	86 5/8" (2200mm)
	8 11/16" (220mm)	78 3/4"-86 5/8" (2000-2200mm)
	9 13/16" (250mm)	78 3/4"-94 1/2" (2000-2400mm)
1/2" (13mm)	7 1/16" (180mm)	94 1/2" (2400mm)

8 FEET



DIMENSIONAL TOLERANCES (EN 13647)

Length: Nominal ± 0.1% / Width: Nominal ± 0.2%

Cupping: Max. 0.2% of nominal width

Banana (bowing): Max. 0.1% of nominal length

Red List Free

0% VOC

EMISSION CLASS FOR BUILDING MATERIAL
M1

INDOOR AIR COMFORT
eurofins
GOLD
CERTIFIED PRODUCT

GREENGUARD
PRODUCT CERTIFIED FOR LOW CHEMICAL EMISSIONS
UL 2818
GOLD

GEV-EMICODE
EC1 PLUS
very low emission



nwfa
National Wood Flooring Association
MEMBER



Geprüft vom Deutschen Institut für Bautechnik

ÉMISSIONS DANS L'AIR INTÉRIEUR*
A+
A+ A B C